

Peddinghaus **PeddiCat**

500 KN IRONWORKER





ELECTRIC LENGTH STOP



CORNER RADIUS TOOL



BENDING ATTACHMENT

Flat Bar
Shear

Section Shear

Bar Stock
Shear

Punch Unit

Notch Unit

Bending
Attachment



Machine Data

Power Rating	4 kW
Charge of Oil	45 l
Net Weight with Oil	820 kg
Machine Dimensions	100 × 68 × 168 cm

Flat Bar Shear

Flat Bar Max	350 × 13 mm
Angle Iron, 45° Cut	100 × 8 mm
Blade Cut Length	370 mm
Working Height	770 mm

Section/Stock Shear

Cross Section	1550 mm ²
Adjustable Stroke	10 - 36 mm
Working Height	1059 mm
with Standard Blades:	
Angle Iron, 90° Cut	100 × 8 mm
Rounds	32 + 17 mm
Squares	30 + 18 mm

Notch Unit

Bending Attachment	10 × 100 mm
Working Height	1035 mm
with Square Notching Attachment:	
Flat Bar	10 mm
Angle	55 × 10 mm
Channels in Flange	80 - 120 mm
I-beams in Flange	80 - 120 mm
Width × Depth	44 × 50 mm

Punch Unit

Adjustable Stroke	10 - 36 mm
Number of Punch Strokes	21 min ⁻¹
Throat Depth	203 mm
Working Height	1035 mm
with Standard Punching Attachment:	
	31 mm Ø in 12 mm
with Oversized Punching Attachment:	
2 1/4	58 mm Ø in 7 mm
2 1/2	65 mm Ø in 6 mm

Peddinghaus

www.peddinghaus.com

Peddinghaus USA • (815) 937-3800 | Peddinghaus UK • +44 1952 200 377 | Peddinghaus Germany • +49 (0) 2332 72-0
Peddinghaus Latin America • +52 81-1001-7087 | Peddinghaus Española • +34 945 465370

PED120919